§415.673

SUBPART BO-ZINC CHLORIDE

	BPT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Milligrams per liter (mg/l)	
TSS	43	25
Arsenic (T)	3.0	1.0
Zinc (T)	11.4	3.8
Lead (T)	1.8	0.6
pH	(1)	(1)

¹ Within the range 6.0 to 10.0

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

§ 415.673 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

SUBPART BO-ZINC CHLORIDE

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Milligrams per liter (mg/l)	
Arsenic (T)	3.0	1.0
Zinc (T)	2.3	0.76
Lead (T)	0.18	0.048

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

§415.674 Pretreatment standards for existing sources (PSES).

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources (PSES):

SUBPART BO-ZINC CHLORIDE

	PSES effluer	6 effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Milligrams per liter (mg/l)		
Arsenic (T)	3.0	1.0	
Zinc (T)	2.3	0.76	
Lead (T)	0.18	0.048	

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

§ 415.675 New source performance standards (NSPS):

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

SUBPART BO-ZINC CHLORIDE

	NSPS effluer	nt limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Milligrams per liter (mg/l)		
TSS	28	17	
Arsenic (T)	3.0	1.0.	
Zinc (T)	2.3	0.76	
Lead (T)	0.18	0.048	
pH	(¹)	(1)	

¹ Within the range 6.0 to 10.0.

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

§415.676 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations for arsenic (T), zinc (T), and lead (T) are the same as specified in §415.674.

§ 415.677 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart must